

IPGS-0204DSFP

4 10/100/1000T + 2 Dual Speed SFP Industrial Switch
w/4 PoE 802.3at/af Injectors



- Complies with IEEE 802.3at/af PoE Standard
- Redundant Power Design
- Built-in boost voltage from 12VDC to 48VDC(12V model)
- Wide operating temperature range from -40°C to 75°C



OVERVIEW

The Lantech IPGS-0204DSFP is a 4 10/100/1000T + 2 Dual Speed SFP with 4 IEEE 802.3at/af High Power PoE Industrial Switch.

The IPGS-0204DSFP is a cost-effective solution, which meets the high reliability requirements demanded by industrial applications. Besides, the equipment meets IEEE 802.3at standard, the switch can provide 30 Watts output per PoE port for Powered Devices. The switch supports wide operating temperature, range from -40°C to 75°C.

The Lantech IPGS-0204DSFP is designed to meet the


demands of Industrial environments, comes packaged in a robust IP30 housing and has been tested extensively to meet Industrial EMI and EMC standards. Rigorous mechanical testing has also been undertaken to comply with free fall, shock and vibration stability test requirements.

With voltage boost design, the IPGS-0204DSFP-12V can work from 12/24V input power source and boost the voltage to 48VDC to feed the POE power over Ethernet cable for any vehicles that usually has 12/24V power source. The slim compact design is able to fit in variety of cabinets and space.

FEATURES & BENEFITS

- Built-in 12 to 48V DC-DC converter for PoE(12V model)
- Embedded 4-port PoE 802.3at inject function
- DIP switch to adjust SFP 100M or 1000M speed
- Back-plane (Switching Fabric): 12Gbps
- Supports wide operating temperature (-40°C~75°C)
- PoE 80W budget for 12V input, 120W for 24V input
- Redundant power with polarity reverse protection
- IP-30 protection with DIN Rail and Wall Mount design
- Relay output for power fail and alarm

DIMENSIONS (unit=mm)



SPECIFICATION

Hardware Specification		Power Consumption	120W (PoE Full load 48V / 24V input); 6W (switch) 80W (PoE full load 12V input)
Switch Architecture	Back-plane (Switching Fabric): 12Gbps Packet throughput ability (Full-Duplex): 17.85 Mpps @64bytes	Operating Humidity	5% to 95% (Non-condensing)
Transfer Rate	14,880pps for Ethernet port 148,800pps for Fast Ethernet port 1,488,000pps for Gigabit Ethernet port	Operating Temperature	-40°C ~ 75°C
Packet Buffer	1Mbits	Storage Temperature	-40°C ~ 85°C
Mac Address	8K MAC address table	Case Dimension	IP30, 43mm (W) x 152mm (H) x 105mm (D)
Connector	10/100/1000T: 4 x RJ-45 Mini-GBIC: 2 x 100/1000 Dual Speed SFP Sockets	Installation	DIN rail or Wall mounting design
DIP Switch	SFP Speed 1000M or 100M	EMC/EMI	FCC Class A, CE EN61000-4-2 (ESD), CE EN61000-4-3 (RS), CE EN-61000-4-4 (EFT), CE EN61000-4-5 (Surge), CE EN61000-4-6 (CS), CE EN61000-4-8, CE EN61000-6-2, CE EN61000-6-4
Protocol	CSMA/CD	Stability Testing	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)
PoE pin assignment	RJ-45 port # 1-# 4 support IEEE 802.3at End-point, Alternative A mode. Per port provides 30W at 54V ability. Positive (VCC+): RJ-45 pin 1,2. Negative (VCC-): RJ-45 pin 3,6.	MTBF	12V model: 1,291,990 hrs 48V model: 1,414,427 hrs
LED	Per unit: Power 1 (Green), Power 2 (Green), Fault (Red) 4 port 10/100/1000T: Link/Activity (Green), Full duplex/Collision (Yellow) ; PoE (Yellow) SFP port: LNK/ACT (Green)	Warranty	5 years
Power Supply	DC 12V~56V(12V model); Redundant power DC45 to 56V; redundant power (48V model)		

ORDERING INFORMATION

- **IPGS-0204DSFP-12V.....P/N: 8350-966**
4 10/100/1000T + 2 Dual Speed SFP Industrial Switch w/4 PoE 802.3at Injectors & 12~48VDC input
- **IPGS-0204DSFP-48V.....P/N: 8350-967**
4 10/100/1000T + 2 Dual Speed SFP Industrial Switch w/4 PoE 802.3at Injectors & 48VDC input

OPTIONAL ACCESSORIES

DIN Rail Power

- **AD1240-48S** 48VDC, 5A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **AD1120-48F** 48VDC, 2.5A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **AD1240-48S-5** 48~56VDC, 4.3A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **AD1360-48S-5** 48~56VDC, 6.5A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **AD1500-48S-5** 48~56VDC, 9A, Wide AC Input, Build-in fan Cooled, DIN Rail or Wall Mounted, RoHS, Operating Temp. -20°C~50°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)

Mini GBIC (SFP)

- | | |
|--|--|
| ■ 8330-162 MINI GBIC 1000SX (LC/0.5km) Transceiver | ■ 8330-189 LTSFP-1000BX-10KM Transceiver (WDM 1550) |
| ■ 8330-163 MINI GBIC 1000SX2 (LC/2km) Transceiver | ■ 8330-186 LTSFP-1000BX-20KM Transceiver (WDM 1310) |
| ■ 8330-165 MINI GBIC 1000LX (LC/10km) Transceiver | ■ 8330-187 LTSFP-1000BX-20KM Transceiver (WDM 1550) |
| ■ 8340-0591 MINI GBIC 1000LHX (LC/40km) Transceiver | ■ 8330-180 LTSFP-1000BX-40KM Transceiver (WDM 1310) |
| ■ 8330-166 MINI GBIC 1000XD (LC/50km) Transceiver | ■ 8330-182 LTSFP-1000BX-40KM Transceiver (WDM 1550) |
| ■ 8330-169 MINI GBIC 1000XD (LC/60km) Transceiver | ■ 8330-181 LTSFP-1000BX-60KM Transceiver (WDM 1310) |
| ■ 8330-167 MINI GBIC 1000ZX (LC/80km) Transceiver | ■ 8330-183 LTSFP-1000BX-60KM Transceiver (WDM 1550) |
| ■ 8330-170 MINI GBIC 1000EZ (120km) Transceiver | ■ 8330-184 LTSFP-1000BX-80KM Transceiver (WDM 1490) |
| ■ 8330-168 MINI GBIC 1000T (100m) Transceiver | ■ 8330-185 LTSFP-1000BX-80KM Transceiver (WDM 1550) |
| ■ 8330-188 LTSFP-1000BX-10KM Transceiver (WDM 1310) | |

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2015 Copyright Lantech Communications Global Inc. all rights reserved.
The revise authority rights of product specifications belong to Lantech Communications Global Inc.
Lantech may make changes to specification and product descriptions at anytime, without notice.